

POLYFOAM PRODUCTS, INC.
THIS MATERIAL SAFETY DATA SHEET PROVIDED AS A GUIDE TO THE USER
PLEASE READ ENTIRE MSDS BEFORE USING THIS PRODUCT
PLEASE CONTACT THE TECHNICAL ASSISTANCE NUMBER FOR ANY ADDITIONAL INFORMATION

Product Name:

POLYSET® AH160 A

THIS MATERIAL IS EITHER MANUFACTURED BY AND OR DISTRIBUTED BY:

Polyfoam Products, Inc.
11715 Boudreaux Road
Tomball, TX 77375

Ph - 281 350 8888

REVISION DATE: MARCH 2, 2006

24 HOUR EMERGENCY RESPONSE: CALL CHEMTREC 800 424 9300

SECTION I IDENTIFICATION

PRODUCT NAME: POLYSET® AH160 A

CHEMICAL FAMILY: Diisocyanate

FORMULA CONFIDENTIAL: Contact Manufacturer for confidential release of information.

SECTION II— HAZARDOUS INGREDIENTS COMPOSITION

HAZARDOUS INGREDIENT	CAS NUMBER	PEL	PERCENT
Polymeric Diphenylmethane Diisocyanate	9016-87-9	not listed	>80
Polymeric Diphenylmethane Diisocyanate CONTAINS APPROX. 45% OF:			
4,4 Diphenylmethane Diisocyanate	101-68-8	0.02ppm	
HCFC-22	75-45-6	not listed	<20
Polyalkyleneoxide- methylsiloxane Copolymer	Trade Secret		<10

POLYFOAM PRODUCTS, INC.

THIS MATERIAL SAFETY DATA SHEET PROVIDED AS A GUIDE TO THE USER

PLEASE READ ENTIRE MSDS BEFORE USING THIS PRODUCT

PLEASE CONTACT THE TECHNICAL ASSISTANCE NUMBER FOR ANY ADDITIONAL INFORMATION

SECTION III — HAZARD - PHYSICAL DATA -

APPEARANCE:	Liquid and gas under pressure	
PHYSICAL FORM:	LIQUID	COLOR: Light Brown
BOILING POINT:	<0° F	
VAPOR PRESSURE	151 psig @ 25°C	
SPECIFIC GRAVITY:	1.23 @ 25°C	
SOLUBILITY IN WATER	Not Soluble. Reacts slowly with water to liberate CO2 gas.	
% VOLATILES BY VOLUME	<20	

SECTION IV – FIRST AID

EYES: FLUSH IMMEDIATELY WITH WATER OR EYE WASH SOLUTION FOR 15 MINUTES. CONTACT WITH EYES MAY CAUSE MODERATE TO SEVERE IRRITATION. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN: WASH OFF IMMEDIATELY WITH SOAP AND WATER FOR AT LEAST 15 MINUTES. REMOVE ALL CONTAMINATED CLOTHING AND SHOES FOR DISPOSAL. FOR SEVERE EXPOSURES, GET UNDER SAFETY SHOWER AFTER REMOVING CLOTHING, THEN GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION: MOVE TO AREA FREE FROM RISK OF FURTHER EXPOSURE. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION AS NEEDED. OBTAIN MEDICAL ATTENTION. ASTHMATIC LIKE SYMPTONS MAY DEVELOP AND MAY BE IMMEDIATE OR DELAYED FOR SEVERAL HOURS. CONSULT PHYSICIAN SHOULD THIS OCCUR.

INGESTION: IF INGESTED DO NOT INDUCE VOMITING - IF THE VICTIM IS CONSCIOUS GIVE HIM/HER A GLASS OF WATER OR MILK – NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET MEDICAL ATTENTION IMMEDIATELY. ALWAYS SEEK MEDICAL ATTENTION WHEN EXPOSED TO THIS OR OTHER CHEMICALS.

POLYFOAM PRODUCTS, INC.

THIS MATERIAL SAFETY DATA SHEET PROVIDED AS A GUIDE TO THE USER

PLEASE READ ENTIRE MSDS BEFORE USING THIS PRODUCT

PLEASE CONTACT THE TECHNICAL ASSISTANCE NUMBER FOR ANY ADDITIONAL INFORMATION

SECTION V – FIRE AND EXPLOSION DATA

FLASHPOINT: >200 DEG F

AUTOIGNITION TEMPERATURE >600 DEG F

EXTINGUISHING MEDIA: SMALL FIRES: USE DRY CHEMICAL POWDER.
LARGE FIRES: USE WATER SPRAY, FOG OR FOAM.
DO NOT USE WATER JET. IF WATER IS USED, VERY
LARGE QUANTITIES ARE REQUIRED. REACTION WITH
WATER MAY BE VIGOROUS. CONTAIN RUNOFF WATER
WITH TEMPORARY BARRIERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

CONTAINERS ARE EQUIPPED WITH A PRESSURE RELIEF
VALVE INTENDED TO VENT ANY EXCESSIVE BUILD UP OF
PRESSURE EXERTED BY GASES GENERATED BY HEAT,
THERMAL DECOMPOSITION OR COMBUSTION.

KEEP EXPOSED CONTAINERS COOLED WITH WATER
SPRAY.

KEEP UNNECESSARY PEOPLE AWAY.

FIRE FIGHTING EQUIPMENT: POSITIVE PRESSURE SCBA'S - FULL PROTECTIVE
CHEMICAL OR FIRE FIGHTING CLOTHING SHOULD BE
WORN BY FIREFIGHTERS. ALL EQUIPMENT MUST BE
THOROUGHLY DECONTAMINATED AFTER USE.

SECTION VI ACCIDENTAL RELEASE MEASURES

PERSONS DEALING WITH MAJOR SPILLS SHOULD WEAR FULL PROTECTIVE
CLOTHING INCLUDING APPROPRIATE RESPIRATORY PROTECTION. EVACUATE THE
AREA. PREVENT FURTHER LEAKAGE SPILLAGE OR ENTRY INTO DRAINS.

CONTAIN AND ABSORB LARGE SPILLAGES ONTO AN INERT, NON FLAMMABLE
ABSORBENT CARRIER SUCH AS EARTH, SAND OR CLAY ABSORBENT. SHOVEL INTO
OPEN TOP DRUMS OR PLASTIC BAGS FOR FURTHER DECONTAMINATION, IF
NECESSARY. WASH SPILLAGE ARE WITH LIQUID DECONTAMINANT. PROPERLY
DISPOSE OF RESIDUES.

NOTIFY APPLICABLE GOVERNMENT AUTHORITIES IF RELEASE IS REPORTABLE.
THE CERCLA RQ FOR 4,4 MDI IS 5000 LBS.

PREPARATION OF DECONTAMINATION SOLUTION: PREPARE A SOLUTION OF
0.2-0.5% LIQUID DETERGENT AND 3-8% CONCENTRATED HOUSEHOLD AMMONIA IN
WATER.

USE OF DECONTAMINATION SOLUTION: ALLOW DEACTIVATED MATERIAL TO STAND
FOR 30 MINUTES BEFORE SHOVELING INTO DRUMS. DO NOT TIGHTEN BUNGS AS
CO2 GAS MAY BE GENERATED.

POLYFOAM PRODUCTS, INC.

THIS MATERIAL SAFETY DATA SHEET PROVIDED AS A GUIDE TO THE USER

PLEASE READ ENTIRE MSDS BEFORE USING THIS PRODUCT

PLEASE CONTACT THE TECHNICAL ASSISTANCE NUMBER FOR ANY ADDITIONAL INFORMATION

SECTION VII – HANDLING – STORAGE – REACTIVITY DATA

STORAGE TEMPERATURE (MIN/MAX) 60°F TO 100°F

AVERAGE SHELF LIFE: 12 MONTHS

SPECIAL SENSITIVITY: IF CONTAINER IS EXPOSED TO HIGH HEAT 400°F OR HIGHER, OR CONTAMINATED WITH WATER, PRESSURE CAN BE GENERATED. CONTAINERS ARE EQUIPPED WITH A PRESSURE RELIEF VALVE INTENDED TO VENT ANY EXCESSIVE BUILDUP OF PRESSURE EXERTED BY GASES GENERATED BY HEAT OR MOISTURE.

PRECAUTIONARY MEASURES: STORE IN TIGHTLY CLOSED CONTAINERS TO PREVENT MOISTURE CONTAMINATION. AVOID CONTACT WITH SKIN AND EYES. DO NOT BREATH AEROSOLS OR VAPORS. THIS MATERIAL CAN PRODUCE ASTHMATIC SENSITIZATION UPON EITHER SINGLE INHALATION EXPOSURE TO A RELATIVELY HIGH CONCENTRATION OR UPON REPEATED INHALATION TO LOWER EXPOSURES TO LOWER CONCENTRATIONS.

EXPOSURES TO VAPORS OR HEATED POLYSET® AH160 A CAN BE EXTREMELY DANGEROUS.

SECTION VIII – EXPOSURE - HEALTH DATA – PERSONAL PROTECTION

LIKELY ROUTES OF EXPOSURE – EYE – SKIN – INHALATION

FOR EYES – LIQUID CHEMICAL GOGGLES OR FULL FACE SHIELD. VAPOR RESISTANT GOGGLES SHOULD BE WORN WHEN CONTACT LENSES ARE IN USE. IN A SPLASH HAZARD ENVIRONMENT, CHEMICAL GOGGLES SHOULD BE USED ALONG WITH A FULL FACE SHIELD.

FOR SKIN – PERMEATION RESISTANT GLOVES (BUTYL RUBBER, NITRILE RUBBER). COVER AS MUCH OF THE EXPOSED SKIN AREA AS POSSIBLE WITH APPROPRIATE CLOTHING.

RESPIRATORY PROTECTION: CONCENTRATIONS GREATER THAN THE 4,4 MDI TLV CAN OCCUR DURING SPRAYING HEATING, OR USE IN A POORLY VENTILATED AREA. IN SUCH CASES WHENEVER THE CONCENTRATION OF 4,4 MDI EXCEEDS THE TLV, RESPIRATORY PROTECTION MUST BE WORN. AN AIR SUPPLIED RESPIRATOR OR SELF CONTAINED BREATHING APPARATUS IS RECOMMENDED. IN SITUATIONS WHERE MATERIAL IS NOT HEATED OR SPRAYED AN AIR PURIFYING RESPIRATOR EQUIPPED WITH AN ORGANIC CARTRIDGE AND PARTICULATE FILTER MUST BE WORN.

HOWEVER, THIS SHOULD BE PERMITTED ONLY FOR SHORT PERIODS OF TIME (LESS THAN ONE HOUR) AT RELATIVELY LOW CONCENTRATIONS AT OR NEAR THE TLV. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE. 929 CFR 1910.134)

POLYFOAM PRODUCTS, INC.

THIS MATERIAL SAFETY DATA SHEET PROVIDED AS A GUIDE TO THE USER

PLEASE READ ENTIRE MSDS BEFORE USING THIS PRODUCT

PLEASE CONTACT THE TECHNICAL ASSISTANCE NUMBER FOR ANY ADDITIONAL INFORMATION

SECTION IX – PHYSICAL AND CHEMICAL PROPERTIES

FORM: LIQUID AND GAS UNDER PRESSURE. LIQUID WILL BECOME FOAMY IS RELEASED FROM CONTAINER.

ODOR: SLIGHT MUSTY ODOR

SOLUBILITY IN WATER: INSOLUBLE. WILL REACT SLOWLY WITH WATER TO FORM CO2 GAS.

SPECIFIC GRAVITY: 1.23 @ 77°F

VISCOSITY: 130 CPS @ 77°F

% VOLATILES: <20%

SECTION X – STABILITY AND REACTIVITY

STABILITY: STABLE AT AMBIENT TEMPERATURES

CONDITIONS TO AVOID: HIGH TEMPERATURES OR FREEZING

INCOMPATIBILITY: REACTS SLOWLY WITH MOISTURE

HAZARDOUS DECOMPOSITION:

MAY PRODUCES CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER ASPHYXIANTS

SECTION XI – TOXICOLOGICAL INFORMATION

AVOID EXPOSURE WITHOUT PROTECTIVE GEAR - REPEATED EXPOSURE TO SKIN OR EYES MAY HAVE HARMFUL - INGESTION HARMFUL - IF INGESTED SEEK IMMEDIATE MEDICAL ATTENTION

EXPOSURE GUIDELINES:

ACGIH TLV 0.05 mg/M³

OSHA PEL 0.20 mg/M³

HARMFUL EFFECTS VARY DEPENDING ON LEVEL OF EXPOSURE – ALWAYS SEEK MEDICAL ATTENTION AFTER EXPOSURE TO CHEMICALS IN ACCORDANCE WITH YOUR COMPANY HEALTH AND SAFETY PROCEDURES.

SECTION XII – ECOLOGICAL INFORMATION

IT IS UNLIKELY THAT SIGNIFICANT ENVIRONMENTAL EXPOSURE IN THE AIR OR WATER WILL ARISE BASED ON CONSIDERATION OF THE USE OF THIS SUBSTANCE.

THIS MATERIAL IS IMMISCIBLE WITH WATER, BUT WILL REACT WITH WATER TO PRODUCE INERT AND NON-BIODEGRADABLE SOLIDS.

POLYFOAM PRODUCTS, INC.

THIS MATERIAL SAFETY DATA SHEET PROVIDED AS A GUIDE TO THE USER

PLEASE READ ENTIRE MSDS BEFORE USING THIS PRODUCT

PLEASE CONTACT THE TECHNICAL ASSISTANCE NUMBER FOR ANY ADDITIONAL INFORMATION

SECTION XIII - DISPOSAL INFORMATION

DISPOSAL SHOULD BE IN ACCORDANCE WITH LOCAL, STATE, PROVINCIAL OR NATIONAL REGULATIONS. THIS MATERIAL IS NOT A HAZARDOUS WASTE UNDER RCRA 40 CFR 261. SMALL QUANTITIES SHOULD BE TREATED WITH A DECONTAMINATE SOLUTION. THE TREATED WASTE IS NOT A HAZARDOUS MATERIAL UNDER RCRA 40 CFR 261.

SECTION XIV - TRANSPORTATION INFORMATION

UN OR ID NUMBER: UN 1956

PROPER SHIPPING NAME: COMPRESSED GAS N.O.S.
CHLORODIFLUOROMETHANE MIXTURE

HAZARD CLASS: CLASS 2.2

REPORTABLE QUANTITY: 5000 LBS.

TRADE NAME: POLYSET® AH160 A

SECTION XV - REGULATORY INFORMATION

THIS PRODUCT IS CLASSIFIED AS HAZARDOUS UNDER OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

TSCA INVENTORY: ALL INGREDIENTS ARE ON THE TSCA INVENTORY OR ARE NOT REQUIRED TO BE LISTED ON THE TSCA INVENTORY.

EPCRA SECTION 313: DIISOCYANATE COMPOUND CODE N120

SECTION XVI OTHER

CAN CAUSE DAMAGE TO LUNGS, RESPIRATORY TRACT, SKIN, EYES.

MAY CAUSE ALLERGIC RESPIRATORY OR SKIN REACTION.

HMIS: HEALTH=2 FIRE=1 REACTIVITY=1

NFPA: HEALTH=2 FIRE=1 REACTIVITY=1 SPECIFIC HAZARD= N/A

THIS DOCUMENT PREPARED BY:

PATRICK M. DONAHUE
PRODUCT MANAGER

DATE PREPARED: 3/2/2006