



July 7, 2010

The particular underlayment specified is critical to the performance of the adhesive-set tile system. The underlayments must be tested to confirm compatibility with the adhesive. The following lists the underlayment manufacturers and the related products that have completed the long-term heat and humid aging test required by Polyfoam and ICC-ES Acceptance Criteria - AC152 meeting the minimum tensile strength requirement of 15 psi. This should not be considered as an endorsement, or a recommendation for any of the underlayments or membranes, but simply a statement that the underlayments/membranes are compatible with the use of the Polyset® AH160 Roof Tile Adhesive.

NOTE #1: Self-adhered underlayments provide higher wind uplift resistance for roof tile applications than a single-layer mechanically attached underlayment. The dynamic action of a mechanically attached underlayment creates a tear effect of the cohesive bond between the adhesive paddy and the underlayment. Therefore, the usage of all single-layer mechanically attached approved underlayments listed below used with Polyfoam Products adhesive-set system is restricted to areas where basic wind speeds are ≤ 100 mph). The single-layered mechanically attached approved underlayment systems listed below are also restricted to slopes 6:12 and below. Additional tile fastening requirements or battens are required for slopes over 6:12.

Note #2: Any Mineral Surfaced Roll Roofing meeting ASTM D249 or ASTM 6380 or Modified Bitumen Underlayment meeting ASTM D6162, D6163, D6164 where our adhesive is bonding to a granular walk surface and passes the granular adhesion test in ASTM D4977 of 1 gram maximum weight loss of granules is allowed.

Note #3: Any Florida Building Code Evaluation Report, ICC-ES Evaluation Report or Metro Dade County N.O.A. approved underlayment that specifically lists use of adhesive-set systems is also approved.

Polyfoam Products Approved Underlayments and Cap Sheets

Polyglass USA, Inc. - Polystick TU; Polystick TU Plus; Polystick TU P; Polyflex SAP; Polyflex G; Elastoflex S6G

Protecto Wrap Company - Rainproof 40; Rainproof 60; Rainproof 120

GAF-Elk - UnderRoof™ 2

CertainTeed - Flintlastic® SA Cap (with ASTM D41 Primer); Flintlastic® SA Cap (with FlintPrime SA Primer); Flintlastic® GMS; Flintlastic® Premium GMS; Flintlastic® FR-P; Flintlastic® Premium FR-P; Flintlastic GTA

Polyfoam Products Approved Underlayments and Cap Sheets “Continued”

InterWrap, Inc. – Titanium PSU-30

Kirsch Building Products, LLC - Sharkskin Ultra™ ; Sharkskin Ultra™ SA

NEI - “TileSeal”

Owens Corning - WeatherLock® Metal; WeatherLock® Specialty Tile and Metal

MonierLifetile - MLT TileSeal™

TARCO Roofing - Leak Barrier Fast 90 Self-adhering Tile Underlayment; PS 200 Self-adhering Underlayment

MFM Building Products – STS™ Underlayment

Mule-Hide Products Co., Inc. – Mule-Hide SA-APP Cap Sheet; Mule-Hide SA-APP Cap Sheet (FR)

Atlas Roofing Corporation - WeatherMaster TU Ultra

Commercial Innovations, Inc. – Viking UDL MT

Soprema, Inc. – Colphene FR GR; Unilay E

The Garland Company – HPR TAM Shield

BITEC, Inc. – MAT-40

IMETCO – DryDek

TREMCO – POWERply SA FR

This list will be upgraded as data is submitted to Polyfoam Products, Inc.

Sincerely,



Riku Ylipelkonen
Manager of Technical Services